

UL Certification

INFINO	Grade	NM-1229I
---------------	-------	----------

Component - Plastics E115797

Guide Information

LOTTE ADVANCED MATERIALS CO LTD

56 Gosan-ro, Uiwang-si Gyeonggi-do 437-711 KR

NM-1229I

Polycarbonate (PC)/Acrylonitrile Butadiene Styrene (ABS), mineral filler "INFINO", furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.0	V-1	-	-	60	60	60
	1.5	V-0	-	-	60	60	60
	2.0-2.2	V-0, 5VB	-	-	60	60	60

Comparative Tracking Index (CTI): -	Inclined Plane Tracking (IPT) kV: -
Dielectric Strength (kV/mm): -	Volume Resistivity (10 ² ohm-cm): -
High-Voltage Arc Tracking Rate (HVTR): -	High Volt, Low Current Arc Resis (D495): -
Dimensional Stability (%): -	

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2016-02-05

Last Revised: 2019-01-07

© 2019 UL LLC



IEC and ISO Test Methods

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	1.0	V-1 (ALL)
			1.5	V-0 (ALL)
			2.0-2.2	V-0, 5VB (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-